


# Headliner Banner Display

## Product Parts

- 1 - Feet (x2)
- 2 - Vertical Poles w/legs (x2)
- 3 - Banner Rails (x2)
- 4 - Clip Hooks (x8)
- 5 - Stakes (x4)
- 6 - Graphic




## Display Set-Up

It's recommended that 2 people assemble this product.


### Step 1

Remove the bottom-most screws and bolts from the Vertical Pole's legs (2). Spread the legs to the length of the Feet (1) and lower the Vertical Pole into the hub on the Foot. Tighten the thumbscrew on the hub to secure the vertical pole. Replace the Support Leg's screws and bolts so that the Support Legs are attached to the feet as shown - the bolt should face away from the stake hole.



### Step 2

Feed the Banner Rails (3) into the Graphic's (6) pole pockets. Insert the edges of the Banner Rails into the couplers on the top and bottom of both Vertical Poles (2).



### Step 3

Loosen the middle thumb screws on the Vertical Poles (2) until you can extend the pole upward. Extend the pole until the banner is taut between the two Banner Rails. Tighten all thumb screws to secure the display's height. Attach the Clip Hooks (4) to the Vertical Poles to align with the Graphic's (6) grommets and hook them on.

### Step 4

With your display in place, drive the Stakes (5) into the holes on the feet, shown in Step 1.

## Storage

Store in a cool dry location.

## Care

Frame or graphic - wipe with a damp cloth.